

## PRODUCT DATA

Article number	Product-name	Dimensions		Content/package unit	Content/pallet unit
		width	length		
698 004	Glava VVS-Tape 50 M	48 mm	50 m	24	1152
698 005	Glava VVS-Tape 75 M	72 mm	50 m	16	768

Material	A dead soft aluminium foil tape coated with a long lasting, ultra violet resistant acrylic adhesive on one side and Lined with a release paper to protect the adhesive face.
Totale tape thickness	0,12 mm (120 µm). Aluminium alone (30 µm)
Color	Aluminium
Tensile Strength	95,5 N / 25 mm
Adhesion to Steel	25 N/25mm (after 24 hours)
Application temperatur	+5 °C to +55 °C (down to 0°C if the surface is free for ice or moisture)
Service temperatur	-20 °C to +120 °C (for short periods up to +140 °C)
Moisture vapour permeability	Less than 1g/m <sup>2</sup> /24 hrs at 38 °C and 90 % RH

### DESCRIPTION / APPLICATION

- A highly specified Aluminium Foil tape for use in any situation where long life, great adhesive strength or ultra violet resistance is required.
- Diffusion resistant no reinforced tape of aluminium classified in *class 1* and *class 0 (BS 476)*.
- *Non-combustible according to IMO FTPC Part 5 – flame spread*
- Long lasting, ultra violet resistant acrylic adhesive
- Lined with a release paper to protect the adhesive face



### Quality Assurance

Glava has EN ISO 9001 and EN ISO 14001 - certificates from NCS (Nemko Certification System).

